Module	Model	Country of origin	Full Auto Calendar	Date display	Illumination	Alarm	Snooze feature	Stopwatch			Count-down timer		World time	Battery type	≈ Battery life (years)	Accuracy	Water-resistant to	Additional functions	Page
								Measuring unit (sec.)	Capacity (hours)	Split time	Capacity (hours)	Repeat function							
1289	DW-6900MM-2ER	TH	•		• (EL)	• (MULTI)		1/100	24	•	24	•		CR2016	2	±15	20 bar	LED indicator (Display Flasher), shock resistant,	03
	DW-6900MM-4ER																	hourly time signal	03
3178	GLS-5500MM-4ER	TH	•		• (AUTO EL)	5 (MULTI)	•	1/100	2 x 1000	•	24	•	•	CR2025	3	±15	20 bar	Yacht timer, low-temperature-resistant to -20 °C,	03
																		LED indicator (Display Flasher), shock resistant,	
																		hourly time signal, button tone on/off	
3263	GD-100-1AER	TH	•		• (LED)	5		1/100	24	•	24		•	CR2025	7	± 15	20 bar	LED indicator (Display Flasher), shock resistant,	04
	GD-100-1BER																	hourly time signal, button tone on/off	04
4778	AW-591ML-1AER	TH	•		• (AUTO LED)	5	•	1/100	1	•	1	•	•	CR1220	3	±15	20 bar	Neobrite, shock resistant, hourly time signal	04
5060	GS-1150-1AER	TH	•	•		•		1/20	24		24		•	CTL920[1]	Solar[2]	RADIO	20 bar	Radio signal reception (EU, USA, Japan, China)	03
																		neobrite, shock resistant	
5146	GA-110C-1AER	TH	•		• (AUTO LED)	5	•	1/1000	100	•	24	•	•	CR1220	2	±15	20 bar	Shock resistant, magnetic-resistant, hourly time signal	04
	GA-110C-7AER																		04

TH = Thailand; [1] storage battery; [2] up to 24 months of power reserve with power save function switched on

Module	Model	Country of origin	Full Auto Calendar	Date display	Illumination	Alarm	Snooze feature	Stopwatch			Count-down timer		World time	Battery type	≈ Battery life (years)	Accuracy	Water-resistant to	Additional functions	Page
								Measuring unit (sec.)	Capacity (hours)	Split time	Capacity (hours)	Repeat function							
3000	BG-5600SA-4ER	TH	•		• (EL)	5	•	1/100	1	•	24		•	CR1616	3	±30	10 bar	Shock resistant, hourly time signal, button tone on/off	05
	BG-5600SA-6ER																		05
	BG-5605SA-1ER																		05
3136	BG-3000A-2ER	TH	•		• (EL)	5		1/100	24	•	24		•	CR1616	3	±30	20 bar	Shock resistant, hourly time signal, button tone on/off	05
	BG-3000A-6ER																		05
3188	BG-1006SA-1ER	TH	•		• (EL)	5	•	1/100	1	•	24		•	CR1616	3	±30	10 bar	Shock resistant, hourly time signal, button tone on/off	04
	BG-1006SA-3ER																		05
	BG-1006SA-4AER																		05
	BG-1006SA-4BER																		05
	BG-1006SA-8ER																		05

TH = Thailand