

Module	Model	Calendar (programmed to the year)	Micro-light	Alarm	Hourly time signal	Snooze feature	Water-resistant to	Stopwatch	Battery life (years)	Battery type	Accuracy	Capacity (hours)	Repeat function	World time	Analogue-digital display	Additional functions	Page
1545	DW-5600E-1VER	2039	• (EL)	• (W/L)	•	•	20 bar	Measuring unit (sec.)	2	CR2016	± 15	24	•	•		Password-protected e-data memory (40 sets); 8-character text with alarm signal	05
2548	G-2000F-1VER; -2VER; -8VER	2039	• (AUTO EL)	5 (W/L)	•	•	20 bar	Capacity (hours)	10	CR2025	± 15	24	•	•		8-character text with alarm signal	07
2737	G-5100-1AVER	2039	• (EL)	5	•	•	20 bar	Split time	2	SR927Wx2	± 15	1	•	•	•	You're times, readable	08
2738	G-5110-2AVER	2039	• (EL)	5	•	•	20 bar	Capacity (hours)	3	SR927Wx2	± 15	1	•	•	•	You're times, readable	08
2759	G-3038-2AVER	2039	• (EL)	5	•	•	20 bar	Measuring unit (sec.)	3	SR927Wx2	± 15	1	•	•	•	You're times, readable	08
2866	GW-700E-1VER; -2VER MTG-9400E-2VER	2039	• (FULL AUTO EL)	5	•	•	20 bar	Capacity (hours)	Solar <sup>1)</sup>	CTL1616 <sup>1)</sup>	RADIO		•	•	•	DCF/MSP radio signal reception, time recorder (30 sets), battery level indicator	04
2869	GW-500E-1VER MTG-9100E-8VER	2039	• (FULL AUTO EL)	5	•	•	20 bar	Measuring unit (sec.)	Solar <sup>1)</sup>	CTL1616 <sup>1)</sup>	RADIO		•	•	•	DCF/MSP radio signal reception, time recorder (30 sets), battery level indicator	04
2943	GL-7500-2BVER	2039	• (AUTO EL)	4	•	•	20 bar	Capacity (hours)	5	CR2025	± 15	1	•	•	•	Moon age display, tide graph, vibration alarm	07
2943	G-7500-1VER; -2VER	2039	• (EL)	4	•	•	20 bar	Measuring unit (sec.)	5	CR2025	± 15	1	•	•	•	e-data memory (80 sets), vibration alarm	07
2957	G-7600-1VER; -2VER; -8VER G-7600B-3VER; -8VER	2039	• (AUTO EL)	5 (W/L)	•	•	20 bar	Capacity (hours)	5	CR2016	± 15	24	•	•	•	Password-protected e-data memory (40 sets)	07
2958	G-8000-1VER; -2VER G-8000-4VER; -8VER G-8000C-2VER; -3VER G-8000B-4VER	2039	• (AUTO EL)	3 (W/L)	•	•	20 bar	Measuring unit (sec.)	5	CR2016	± 15	24	•	•	•	You're times, LED indicator	06
2972	GW-6000E-1VER	2039	• (FULL AUTO EL)	5	•	•	20 bar	Capacity (hours)	Solar <sup>1)</sup>	CTL1616 <sup>1)</sup>	RADIO	1	•	•	•	DCF/MSP radio signal reception, battery level indicator	04
3017	GW-554E-1VER; -2VER GW-554E-3VER; -4VER	2039	• (FULL AUTO EL)	5	•	•	20 bar	Measuring unit (sec.)	Solar <sup>1)</sup>	CTL1616 <sup>1)</sup>	RADIO	1	•	•	•	DCF/MSP radio signal reception, battery level indicator	03
3364	GW-1400E-2AVER GW-1400DE-1AVER; -2AVER GW-1400DE-4AVER	2039	• (SUPER FULL AUTO LED)	•	•	•	20 bar	Capacity (hours)	Solar <sup>1)</sup>	CTL1616 <sup>1)</sup>	RADIO		•	•	•	DCF/MSP radio signal reception, battery level indicator	04
3750	G-300-2AVER; -3AVER G-300L-2AVER G-353B-1AVER	2039	• (EL)	5	•	•	20 bar	Measuring unit (sec.)	2	SR927Wx2	± 15	1	•	•	•	You're times, readable	09
3751	G-350-2AVER G-350L-2AVER; -4AVER	2039	• (EL)	5	•	•	20 bar	Capacity (hours)	2	SR927Wx2	± 15	1	•	•	•	You're times, readable	08
3752	G-5310-4AVER G-7910-2AVER	2039	• (EL)	5	•	•	20 bar	Measuring unit (sec.)	2	SR927Wx2	± 15	1	•	•	•	You're times, readable	08
4361	GW-17000E-1AVER; -2AVER	2039	• (SUPER ILLUMINATOR)	•	•	•	20 bar	Capacity (hours)	Solar <sup>1)</sup>	CTL1025 <sup>1)</sup>	RADIO	1	•	•	•	DCF/MSP radio signal reception, battery level indicator	03
4367	G-3048L-1A1VER G-3148L-1AVER G-3548L-5AVER	2039	• (EL)	5	•	•	20 bar	Measuring unit (sec.)	2	SR927Wx2	± 15	1	•	•	•	You're times	05
4368	G-3158L-2AVER; -4AVER	2039	• (EL)	5	•	•	20 bar	Capacity (hours)	2	SR927Wx2	± 15	1	•	•	•	You're times	05

<sup>1)</sup> up to 24 months of power reserve with power save function switched on; <sup>2)</sup> storage battery